

Engine Power	194KW
Rotation Torque	3,000 N~m
Drill Type	Top hammer
Applications	Mining and quarrying
Air Pressure	10.5 Bar
Air Flow	10.5m³/min

RD45A-CS TOP HAMMER



TOUGH WORLD. TOUGH EQUIPMENT.

RD45A-CS SPECIFICATIONS >>>

DIESEL ENGINE	
Manufacturer	Commins
Engine model	QSC8.3-260III
Rated power	62.5 kw
Fuel tank capacity	400L

OVERALL DIMENSION	
Length	9200mm
Width	2350mm
Height	3100mm
Weight	12500kg




UNDERCARRIAGE	
Tramming speed	4.3/2.8 km/h
Track oscillation	±10°
Ground clearance	420 mm
Max. gradeability	30°/12°
Crawler width	330mm

FUNCTIONAL SPEC	RD45A-CS
Hole ranges	76-127 mm
Rob Spec	T45, T51

FUNCTION OF BOOM	
Feed travel	4420 mm
Feed force, max.	16kN
Pull up force, max.	21 kN

DRIFTER SPEC	
Model	Yamamoto YH-100
Impact power	20.6kw
Impact frequency	2500bpm
Rotary speed	0-150rpm

COMPRESSOR ASSEMBLY	
Manufacturer	Sullivan-Platek
Air flow	10.5 m³/min
Air pressure	10.5 bar



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
 T: +86 772 3886124 E: overseas@liugong.com
 www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. Liugong standard and optional equipment may vary from region to region. Please consult your Liugong dealer for information specific to your area.

06/2019 Designed by LiuGong